

# MODEL 1221 CENTRIFUGE SYSTEM

## STANDARD SPECIFICATIONS

**G-Range:** 0 to 250 G's at 25-inch radius

**Payload Capacity:** 18 inch cube (457 mm), 200 lbs. (91 Kg) per arm

**Maximum G-lbs.:** 20,000 G-lbs.

**Rate Range:** 0-600 RPM

**Slip Rings:** 54 lines at 2A per line and 10 lines at 5A per line

**Drive System:** 15 H.P. D.C. motor

**Control:** AERO 4000 Controller with centrifuge-specific GUI

**Testing radius:** UUT location is adjustable within mounting platform,  
15-33 inch radius (381-838 mm)

**Stability:**  $\leq 0.1\%$  of operating rate above 60 rpm. Zero Drift.

**Speed Indication Accuracy:**  $0.01\% \pm 0.02$  RPM (measured over 1 revolution)

**Mounting Platform:** 18 inches x 18 inches horizontal platforms located at each end of the rotating arm

**Power:** 230VAC, 3 phase, 60 Hz, 65 A (70 A service)

### **Dimensions:**

Centrifuge: 73 in. diameter x 72 in. high (1854 x 1829 mm)

Console: 24 in. wide x 30 in. deep x 70 in. high (610 x 762 x 1778 mm)

Drive isolation Transformer: 26 in. wide x 22 in. deep x 34.5 in. high (660 x 559 x 876 mm)

**Approximate Weight:** 3500 lbs (1588 Kg)

**Other Standard Features:** Unbalance Sensor provides automatic machine shut down in event of unbalanced loads; Electrical door interlocks prevent enclosure from being opened while machine is in motion; Dynamic Braking System



## MODEL 1221 OPTIONS:

- Custom slip ring configuration
- Wireless camera viewing system
- Fluid transfer joint
- Coaxial rotary joint
- Positionable platforms

This Centrifuge System was formerly manufactured by Trio Tech International and Genisco Technology Corporation

For additional information or special requirements, contact Ideal Aerosmith. Specifications subject to change without notice. Please call for pricing.

Rev: F