

MODEL 1221 CENTRIFUGE SYSTEM

STANDARD SPECIFICATIONS

G-Range: 0 to 250 G's at 25-inch radius

Payload Capacity: 18 inch cube (457 mm),
200 lbs. (91 Kg) per arm

Maximum G-lbs.: 20000 G-lbs.

Rate Range: 0-600 RPM

Slip Rings: 54 lines at 2A per line and 10 lines at 5A
per line

Drive System: 15 H.P. D.C. motor

Control: AERO 4000 Controller with centrifuge-
specific GUI

Testing radius: UUT location is adjustable within
mounting platform, 15-33 inch radius (381-838 mm)

Stability: $\leq 0.1\%$ of operating rate above 60 rpm. Zero
drift.

Speed Indication Accuracy: $0.01\% \pm 0.02$ RPM
(measured over 1 revolution)

Vibration Isolation: Less than 0.1 G from 0.5 – 100 Hz Bi-Axial measured at UUT Mounting Platform

Mounting Platform: 18 inches x 18 inches horizontal platforms located at each end of the rotating arm

Power: 230VAC, 3 phase, 60 Hz, 65 A (70 A service)

Dimensions:

Centrifuge: 73 in. diameter x 72 in. high (1854 x 1829 mm)

Console: 24 in. wide x 30 in. deep x 70 in. high (610 x 762 x 1778 mm)

Drive isolation Transformer: 26 in. wide x 22 in. deep x 34.5 in. high (660 x 559 x 876 mm)

Approximate Weight: 3500 lbs (1588 Kg)

Other Standard Features: Unbalance Sensor provides automatic machine shut down in event of unbalanced loads; Electrical door interlocks prevent enclosure from being opened while machine is in motion; Dynamic Braking System



MODEL 1221 OPTIONS:

- Custom slip ring configuration
- Camera viewing system
- Fluid transfer joint
- Coaxial rotary joint
- Positionable platforms

This Centrifuge System was formerly manufactured by Trio Tech International and Genisco Technology Corporation

For additional information or special requirements, contact Ideal Aerosmith. Specifications subject to change without notice. Please call for pricing.

Rev G