

MODEL 1231 CENTRIFUGE SYSTEM

STANDARD SPECIFICATIONS

g-Range: 0 to 200 g's at 44-inch (1118 mm) radius

Maximum g-lbs: 20000 g-lbs

Payload Capacity: 24 inch cube, (610 mm);
200 lbs. (91 Kg) per arm

Rate Range: 0-400 RPM

Slip Rings: 108 lines at 3A per line

Drive System: 15 H.P. D.C. motor

Control: AERO 4000 Controller with centrifuge-specific GUI

Testing radius: UUT location is adjustable within mounting platform, 30-54 inch radius (762-1372 mm)

Stability: $\leq 0.1\%$ of operating rate above 40 rpm. Zero drift.

Speed Indication Accuracy: $0.01\% \pm 0.02$ RPM
(measured over 1 revolution)

Vibration Isolation: Less than $0.1g$ from 0.5 – 100 Hz

Bi-Axial measured at UUT Mounting Platform

Power: 230VAC, 3 phase, 60 Hz, 65 A (70 A service)

Mounting Platform: 24 inches x 24 inches horizontal platforms located at each end of the rotating arm

Dimensions:

Centrifuge: 122.2 in. wide x 121.2 in. deep x 78.6 in. high (3103 x 3078 x 1996 mm)

Console: 24 inches wide x 30 inches deep x 70 inches high (610 x 762 x 1778 mm)

Drive isolation Transformer: 26 in. wide x 22 in. deep x 34.5 in. high (660 x 559 x 876 mm)

Approximate Centrifuge Weight: 6100 lbs. (2765 Kg)

Other Standard Features: Unbalance Sensor provides automatic machine shut down in event of unbalanced loads; Electrical door interlocks prevent enclosure from being opened while machine is in motion; Dynamic Braking System



MODEL 1231 OPTIONS:

- Custom slip ring configuration
- Camera viewing system
- Fluid transfer joint
- Coaxial rotary joint
- Positionable platforms

This Centrifuge System was formerly manufactured by Trio Tech International and Genisco Technology Corporation

For additional information or special requirements, contact Ideal Aerosmith. Specifications subject to change without notice. Please call for pricing.

Rev L